

iceValet®

HD22 - 22" Hotel Dispenser

iceValet® Hotel Dispenser



Features

- Stores up to 120 lb. of cube ice.
- Simple push chute for easy ice dispensing.
- Modern, stylish design in a corrosion resistant metallic cabinet.
- Removable top panel allows access to the bin for easy cleaning without having to remove the ice machine.
- Improved sink depth that will accommodate almost every size hotel ice bucket.
- Equipped with an 11 ft. power cord.
- Match the iceValet® dispenser with a Scotsman Prodigy Plus® ice machine featuring self-monitoring technology, cost-saving energy efficiency, extended time between cleanings, easy-access servicing and built-in anti-microbial protection. All of these features add up to the smartest choice in ice.

Easy Push Chute



Storage Capacity

HD22

Application Bin Capacity

120/59
lb/kg



Matching Ice Machine Options

Model Number	Cube Size	Condenser Type	24 Hr Ice Production		
			70°F/21°C 50°F/10°C lb/kg	Air Water	90°F/32°C 70°F/21°C lb/kg
C0322MA	Medium	Air	356/162		255/116
C0322MW	Medium	Water	366/166		329/150
C0322SA	Small	Air	356/162		255/116
C0322SW	Small	Water	366/166		329/150
C0522MA	Medium	Air	475/216		380/173
C0522MW	Medium	Water	549/250		494/225
C0522SA	Small	Air	475/216		380/173
C0522SW	Small	Water	549/250		494/225



Polyurethane Insulation

Foam insulation is forced between the wall and liner under heat and pressure to form a perfect wall to wall bond, preserving ice supply for long periods.



Certification



Warranty

- 3 years parts and labor on all components.
- Warranty valid in North, South & Central America for commercial installations.
- Contact factory for warranty in other regions.
- Residential Applications: 1 year parts and labor

Scotsman®


- 101 Corporate Woods Parkway, Vernon Hills, IL 60061 •
- 1-800-SCOTSMAN • Fax: 847-913-9844 • www.scotsman-ice.com • customer.relations@scotsman-ice.com •

HD22 - 22" Hotel Dispenser

HD22 - 22" Hotel Dispenser

iceValet® Hotel Dispenser

Installation Note: Allow 6" space at left, back and right side for ventilation and utility connections.



C0322 on HD22 hotel dispenser.



Specifications

Model Number	Actuation	AHRI Bin Capacity lb/kg	Electrical	Circuit Wires	Min. Circuit Ampacity	Max. Fuse Size or HACR Circuit Breaker (amps)
HD22B-1	Push	120/59	115/60/1	2	Cord	15



All Models

Dimensions (W x D x H):

Unit: 22" x 33.5" x 47.25"
(55.9 x 85.1 x 120.0 cm)

Shipping Carton: 25" x 37" x 53"
(63.5 x 94 x 134.6 cm)

Shipping Weight: 201 lb / 91 kg



Operating Requirements

	Minimum	Maximum
Air Temperatures	50°F (10°C)	100°F (38°C)
Water Temperatures	40°F (4.4°C)	100°F (38°C)
Remote Cond. Temps	-20°F (-29°C)	120°F (49°C)
Water Pressures	20 PSIG (1.4 bar)	80 PSIG (5.5 bar)
Electrical Voltage	-5%	+10%

Specifications and design are subject to change without notice.

Scotsman recommends all ice machines have water filtration. See Scotsman water filter specification sheet for details.